


# BTEMXX

EARTH BOND Setting



► BATTERY SETTING TOOL FOR M6, M8 AND M10 EARTH BOND

3 IN 1 TOOL



MADE IN FRANCE

## TECHNICAL CHARACTERISTICS

THREAD	M6 - M8 - M10
FORCE	Adjustable 10kN to 25kN
STROKE	8 mm
CYCLE TIME	2 secondes
AUTONOMIE (approx.)	> 1000 setting
BATTERY	18V Li-Ion 2.0Ah
OPERATING TEMPERATURE	-10°C / +50°C
POIDS (tool in use)	3,400 kg
WEIGHT (tool in a case)	6,200 kg
DIMENSIONS (L x l x H in mm)	375 x 75 x 260
REFERENCE	BTEMXX0A
CHARGING TIME	40 min
NOZE AND SLEEVE	Interchangeable

## STRENGTHS

- UNIVERSAL tool for setting filed or tapped Earth bond, metric or imperial
- Color coding on nose and sleeve for easy adjustment of the tool to the type of Earth bond
- Simple change of setting and adjustment of the tool using the adjustment screw
- Automatic screwing by "push-pull" system
- Ergonomic and balanced design for optimal handling
- Guaranteed setting force with automatic return and unscrewing
- High performance battery (5.0Ah optional)
- Tool status indicator light
- LED work area illumination

## SETTING CAPACITY

	M6	M8	M10
COLOR	YELLOW	BLUE	GREEN
SETTING	10 kN	18 kN	25 kN
SLEEVE	94874	94875	94876
NOZE	94877	94878	94879

\* M5 - 10/32UNF - 1/4" - 5/16" - 3/8" please consult us



Tool supplied in a case with accessories for setting M6, M8 and M10 male and female EB

## CONTROL DYNAMOMETER (optional)



REFERENCE	80928 (in case)
WEIGHT	4,700 kg
DIMENSIONS (L x l x H in mm)	380 x 300 x 80
CONTROL OF TOOL	PMTC6 - PMT8 - PMT10 PMTXX - PMA10 - BTEMXX