



HDR SERIES

CONTRACTOR GRAPPLES

THE ORIGINAL AND STILL THE BEST

With a proven design and a new mounting geometry, Universal HDR Grapples have been engineered to withstand rough usage and its enhanced design includes a two-tine moveable upper half and a stationary lower half with three-tines. As the industry's go-to workhorse for more than 50 years, the HDR Series Contractor Grapples are still Made in the USA with global materials. This grapple is remarkably versatile, making it the preferred choice for various applications, from residential/commercial demolition and land clearing to scrap, rock, and waste handling.

HDR SERIES

CONTRACTOR GRAPPLES

Fleet Modularity
Whether it's pin direct or pin grabber quick couplers, this equipment can work on multiple machines by just changing a pin kit

Heavy Duty Pivot Group
significantly reduces stresses and increases pin life

Heavy Duty Torque Tube
for long service life



Modernize the way you arm your fleet for material handling with our Universal HDR Grapple, featuring an enhanced design.

Thick, Bridged Mounting Lugs
for strength and support

Internal Baffle / Stiffener Plates
provide structural reinforcement

Box Tine Construction
can withstand full breakout force of excavator on each tine.



Model	Weight*		Jaw Opening (min)**		Closed Grip Ø (min)		Capacity**		2-Tine Width		3-Tine Width		Min Excavator Weight - 3 rd Member***	
	lbs	kg	in	mm	in	mm	yd ³	m ³	in	mm	in	mm	lbs	m Tons
HDR 200	3,500	1,600	108	2,470	11.5	290	2 - 3	1.5 - 2.3	31	790	45	1,140	32,000	15
HDR 250	4,500	2,000	114	2,900	12.5	320	2.5 - 3.5	1.9 - 2.7	31	790	45	1,140	45,000	21
HDR 350	6,200	2,800	127	3,230	12.5	320	3.5 - 5.5	2.7 - 4.2	33	840	49	1,240	65,000	30
HDR 450	7,600	3,500	140	3,560	16	410	5.5 - 6.5	4.2 - 5	35	890	53	1,350	75,000	35

*Weight includes standard excavator mounting bracket. Attachment weight may vary depending on mounting configuration as well as options.

**Jaw Opening and capacity will vary depending on excavator mounting and the handled material make up.

*** Excavator weight range should be used as a guide only; all mounting configurations must be preapproved by LaBounty.

LaBounty reserves the right to improve, update, or change the product specifications, appearance, or functional attributes without notice.

LABOUNTY

1538 Hwy 2 // Two Harbors, MN 55616 // 833-723-1843 // www.stanleyinfrastructure.com