



[www.stanleyinfrastructure.com/brands/labounty](http://www.stanleyinfrastructure.com/brands/labounty)



# HDR SERIES


## CONTRACTOR GRAPPLES

### PROVEN DESIGN & NEW MOUNTING GEOMETRY

The HDR Grapples have been engineered to withstand rough usage and comprise a movable upper half with two tines and a stationary lower half with three tines. This grapple model has been the industry's go-to workhorse for years and has proven to be remarkably versatile, making it the preferred choice for various applications, including but not limited to demolition (both residential and industrial), scrap handling, rock handling, waste handling, and land clearing.

# HDR SERIES

# CONTRACTOR GRAPPLES



**Fleet Modularity**  
With the ability to change the pin kit, the same grapple can be used for both Quick Coupler and Direct Pin-on configurations


**Heavy Duty Pivot Group**  
significantly reduces stresses and increases pin life

**Heavy Duty Torque Tube**  
for long service life

**Thick, Bridged Mounting Lugs**  
for strength and support

**Internal Baffle / Stiffener Plates**  
provide structural reinforcement

**Box Tine Construction**  
can withstand full breakout force of excavator on each tine.



| Model   | Weight* |       | Jaw Opening (min)** |       | Closed Grip Ø (min) |     | Capacity**      |                | 2-Tine Width |     | 3-Tine Width |       | Min Excavator Weight - 3 <sup>rd</sup> Member*** |        |
|---------|---------|-------|---------------------|-------|---------------------|-----|-----------------|----------------|--------------|-----|--------------|-------|--|--------|
|         | lbs     | kg    | in                  | mm    | in                  | mm  | yd <sup>3</sup> | m <sup>3</sup> | in           | mm  | in           | mm    | lbs  | m Tons |
| HDR 200 | 3,500   | 1,600 | 108                 | 2,470 | 11.5                | 290 | 2 - 3           | 1.5 - 2.3      | 31           | 790 | 45           | 1,140 | 32,000   | 15     |
| HDR 250 | 4,500   | 2,000 | 114                 | 2,900 | 12.5                | 320 | 2.5 - 3.5       | 1.9 - 2.7      | 31           | 790 | 45           | 1,140 | 45,000   | 21     |
| HDR 350 | 6,200   | 2,800 | 127                 | 3,230 | 12.5                | 320 | 3.5 - 5.5       | 2.7 - 4.2      | 33           | 840 | 49           | 1,240 | 65,000   | 30     |
| HDR 450 | 7,600   | 3,500 | 140                 | 3,560 | 16                  | 410 | 5.5 - 6.5       | 4.2 - 5        | 35           | 890 | 53           | 1,350 | 75,000   | 35     |

\*Weight includes standard excavator mounting bracket. Attachment weight may vary depending on mounting configuration as well as options.

\*\*Jaw Opening and capacity will vary depending on excavator mounting and the make up of the material being handled.

\*\*\* Excavator weight range should be used as a guide only, all mounting configurations must be preapproved by LaBounty.

LaBounty reserves the right to improve, update, or change the product specifications, appearance, or functional attributes without notice.