



STANLEY. Infrastructure

SPECIFICATIONS

Impact Energy Class	ft - lb	550	
		750	
Blows Per Minute	bpm	650 - 1550	
Flow Range	gpm	10 - 22	
	lpm	38 - 83	
Hydraulic Operating Pressure	psi	1500 - 2000	
	bar	100 - 140	
System Relief Pressure	psi	2800	
(min. cracking)	bar	180	
Oil Temperatures (max.)	F	190	
	С	88	
Hose Diameter (min.)	inch	3/4	
	mm	19	
Adapter Fitting Size and Type	Male ORFS -12, 1-3/16 -12 UNF		
Weight –	lb	773	
Skid Steer Model (with tool)	kg	351	
Weight –	lb	465	
Side Plate Model (with tool)	kg	210	
	inch	54.4	
	inch mm	54.4 1380	
(with tool)			
(with tool)	mm	1380	
(with tool) Tool Diameter	mm inch	1380 2.7	
(with tool) Tool Diameter	mm inch mm	1380 2.7 70	
Length - Side plate Model (with tool) Tool Diameter Tool Working Length Main Accumulator Charge	mm inch mm inch	1380 2.7 70 15	
(with tool) Tool Diameter Tool Working Length Main Accumulator Charge	mm inch mm inch mm	1380 2.7 70 15 381	
(with tool) Tool Diameter Tool Working Length Main Accumulator Charge Pressure	mm inch mm inch mm psi	1380 2.7 70 15 381 200 +/- 10	
(with tool) Tool Diameter Tool Working Length Main Accumulator Charge Pressure Sound Power Level (LW)	mm inch mm inch mm psi bar	1380 2.7 70 15 381 200 +/- 10 13.8 +/- 0.7	
(with tool) Tool Diameter Tool Working Length Main Accumulator Charge Pressure Sound Power Level (LW)	mm inch mm inch mm psi bar dBA	1380 2.7 70 15 381 200 +/- 10 13.8 +/- 0.7 126	
(with tool) Tool Diameter Tool Working Length Main Accumulator Charge Pressure Sound Power Level (LW) Carrier Size - Skidsteer	mm inch mm inch mm psi bar dBA lb	1380 2.7 70 15 381 200 +/- 10 13.8 +/- 0.7 126 4500 - 7000	
(with tool) Tool Diameter Tool Working Length Main Accumulator Charge Pressure Sound Power Level (LW) Carrier Size - Skidsteer	mm inch mm inch mm psi bar dBA lb	1380 2.7 70 15 381 200 +/- 10 13.8 +/- 0.7 126 4500 - 7000 2045 - 3182	
(with tool) Tool Diameter Tool Working Length	mm inch mm inch mm psi bar dBA lb kg	1380 2.7 70 15 381 200 +/- 10 13.8 +/- 0.7 126 4500 - 7000 2045 - 3182 5000 - 13500	

NOTE:

Weights, dimensions and operating specifications listed on this sheet are subject to change without notice. Where specifications are critical to your application, please consult the dealer.

MBF5 MOUNTED BREAKER

ORDERING INFORMATION













MBF5E00	MBF5S02	MBF5E04	MBF5S04	MBF5E05	MBF5S05
Excavator, side plated breaker with flat top bolt flange for mounting brackets	Fixed skid steer cradle, side plated breaker	Excavator with CP027 top	Skid steer with CP027 top	Excavator with exchange top	Skid steer with exchange top

Note: A conical bit is included in the mounted breaker models listed.

ACCESSORIES



69863	69864	69865	69866	69867	72911	72912	72508	72509
Conical Bit	Cross Cut Chisel Bit	Line Cut Chisel Bit	Blunt Bit	Tamping Pad	Asphalt Cross Cut Bit	Asphalt Line Cut Bit	Cross cut Chisel bit 72"	Thumper Bit, 5" Dia. 22" Working

70984	34892	69858	69859
Seal Kit	Charging Kit	Upper Tool Stop Bushing MBF5/ MB05	Lower Tool Bushing MBF5/MB05

Your authorized Stanley Dealer

STARLEY Infrastructure

3810 SE Naef Road Milwaukie, OR 97267 USA Tel. +1 503.659.5660 Fax +1 503.652.1780

www.stanleyhydraulics.com

MTD/2.2017-2018