

SRP2240/3050/3860/5960

# REVERSIBLE PLATE COMPACTORS

December 2015

## Stanley Light and Medium Reversibles: Maximum Versatility and Performance



Stanley SRP3860

### FEATURES:

1. Foldable and adjustable operating handle, easily transitions from forward to reverse motion
2. Powerful Honda engines (GX120 and GX270 available)
3. Two shaft exciter designed for long service intervals
4. Sturdy housing to protect centrifugal clutch and wear resistant v-belt
5. Wear resistant and self cleaning base plate



- 2 models standard with Honda engine
- SRP: Light weight model ideal for some or confined areas with 4,900 lbs of force
- SRP3860: Top of the light compaction line with 8,500 lbs. of force for up to 20 in. of max compaction

SRP2240/3050/3860/5960

# REVERSIBLE PLATE COMPACTORS

December 2015

## Stanley Heavy Reversibles: Performance Plus Easy Handling



### FEATURES:

1. Foldable and adjustable operating handle, easily transitions from forward to reverse motion
2. Protective casing: protects key components from dirt and damage, allows for easy accessibility and service
3. Powerful Hatz 1 B 40 diesel engine
4. Two shaft exciter designed for long service intervals
5. Sturdy housing to protect centrifugal clutch and wear resistant v-belt
6. Wear resistant and self cleaning base plate, designed for balance and maximum gradient climbing capability

- 2 models standard with electric start and Hatz diesel engines
- Easy change in direction and high climb ability
- SRP4960: 11,000 lbs. of force 24 in. max compaction
- SRP5960: 13,000 lbs. of force 28 in. max compaction





# SRP2240/3050/3860/5960 REVERSIBLE PLATE COMPACTORS

December 2015



## ORDERING AND SPECIFICATIONS

Model Number	SRP2240	SRP3050	SRP3860	SRP4960	SRP5960
Full Model Number	SRP22401H	SRP30501H	SRP386001H	SRP49601D	SRP59601D
Engine	Honda GX120	Honda GX270	Honda GX270	Hatz 1 B 40	Hatz 1 B 40
Engine Starter	Recoil	Recoil	Recoil	Electric	Electric
Fuel Type	Gasoline	Gasoline	Gasoline	Diesel	Diesel
Operating Weight lb. / (kg)	220 / (100)	440 / (200)	580 / (263)	910 / (413)	1,016 / (461)
Working Width with Extension Plates in. / (mm)	16 / (400)	24 / (600)	24 / (600)	24 / (600)	24 / (600)
Frequency VPM / (Hz)	5,880 / (98)	5,400 / (90)	3,900 / (65)	3,900 / (65)	3,900 / (65)
Centrifugal Force lbs. / (kN)	4,900 / (22)	6,700 / (30)	8,500 / (38)	11,000 / (49)	13,000 / (59)
Maximum Compaction Depth in. / (cm)	8 / (20)	14 / (35)	20 / (50)	24 / (60)	28 / (70)
Operating Speed ft./min / (m / min)	82 / (25)	72 / (22)	85 / (26)	98 / (30)	108 / (33)
Max Grade (%)	35	30	35	30	30

Specifications and features are subject to change without notice.

## ACCESSORIES

Model Number	Part Number	Description	Model Number	Part Number	Description
SRP2240	75885	Transport Wheels	SRP4960/5960	75300	Vulcolan Mat 18 in. / (45 cm)
SRP2240	75886	Vulcolan Mat 16 in. / (40 cm)	SRP4960/5960	75887	Vulcolan Mat 24 in. / (60 cm)
SRP3050	76346	Vulcolan Mat 20 in. / (50 cm)	SRP4960/5960	75083	Vulcolan Mat 30 in. / (75 cm)
SRP3050	76350	Vulcolan Mat 24 in. / (60 cm)			

All Stanley Hydraulic Tools, parts, accessories and allied equipment are subject to design improvements, specifications and price changes at any time without notice and with no obligation to units already sold. Weights, dimensions and operating specifications listed herein are subject to change without notice. Where specifications are critical to your applications, please consult Stanley Hydraulic Tools.