

STANLEY®



TJ12 TRACK JACK

The TJ12 is a top-performing track jack with an exceptional power-to-weight ratio, outclassing its competitors. It is designed for durability, with a tool life that is 200% longer than that of leading competitors. The new carry handle improves ergonomics, making it easier to transport from job to job.

TJ12 TRACK JACK

FEATURES AND BENEFITS

- Integrated pump/carry handle increases tool durability and improves ergonomics
- Improved linkage design eliminates potential to bend piston
- Enhanced Disogren O-rings, bushings, and threaded pick-up tube are incorporated to improve the tool's longevity
- Redesigned release knob for quick and easy lowering
- Long-travel pump action means fewer pumps to achieve maximum height
- Internal reservoir bladder allows operation in any position
- 10 tons of lifting force

SPECIFICATIONS

| STROKE (TOTAL LIFT) | 8.8 IN. / 22.3 CM |
|---|--------------------|
| AMOUNT OF TRAVEL PER PUMP STROKE | .16 IN. / .4 CM |
| LIFTING CAPACITY | 10 TONS / 9072 KG |
| WEIGHT | 43 LBS / 19.5 KG |
| OPERATING PRESSURE | 7250 PSI / 499 BAR |
| MAXIMUM HANDLE EFFORT FOR FULL LOADSURE | 75 LBS / 334 N |
| MAXIMUM TOE HEIGHT | 1.81 IN. / 4.59 CM |
| OVERALL COLLAPSED HEIGHT | 14.7 IN. / 37.3 CM |
| BASE WIDTH (STANDARD VERSION) | 6 IN. / 15.2 CM |
| BASE WIDTH (NARROW VERSION) | 4.5 IN. / 11.4 CM |
| BASE LENGTH | 11 IN. / 27.9 CM |

ORDER INFORMATION

| PART NO. | DESCRIPTION |
|----------|--|
| TJ1211S | TRACK JACK, INTEGRAL PUMP, HYDRAULIC JACK |
| TJ1212S | TRACK JACK, INTEGRAL PUMP, NARROW BASE BRIDGE JACK |