

GT18 Power Unit

The GT18 power unit is designed for continuous duty operation of any hydraulic tool in the Type I or Type II category or wherever 8 GPM @ 2000 psi of hydraulic power is required. World class cooling puts the GT18 far ahead of all other power units on the market.

Features:

- Type I or Type II hydraulic circuit with superior cooling
- Electronically controlled engine speed provides 5 or 8 GPM
- Auto idle feature lower fuel consumption and less noise
- Tool circuit lockout during engine startup safety feature
- Quartz hour meter on control panel records engine run time
- Lift & Latch handle with fold-up side handles
- 35-AH sealed, non-spillable, no maintenance battery located in covered compartment
- Electric start engine has pressure lubrication system, low engine oil shut down & spin on oil filter
- In tank hydraulic filter with dipstick and easy access filter replacement
- GT18B05 has Powerlink Inverter system 1000 watt continuous and 1500 watt intermittent power through GFCI receptacles



Specifications:

Output Capacity	5 or 8 GPM / 20 or 30 lpm
Pressure	2,000 psi / 140 bar
Circuit Type	Open Center
Hydraulic Reservoir Capacity	3 Gallons / 11 Liters
Couplers	HTMA Flush Face
Fuel Tank Capacity	7 Gallons / 26.5 Liters
Engine	B&S 18 HP Vanguard or Honda GX620 OHV
Weight	330 lbs / 150 kg
Length	35 in / 89 cm
Width	21.5 in / 54.6 cm
Height	29 in / 73.7 cm
Heat Rejection	5 hp

Stanley Hydraulic Tools 3810 SE Naef Road Milwaukie, OR 97267

503.659.5660 Fax 503.652.1780 www.stanleyhydraulic.com



ORDERING INFORMATION:

PART NUMBER	DESCRIPTION
GT18B02	5 or 8 GPM Briggs & Stratton 18 HP
GT18B05	5 or 8 GPM Briggs & Stratton 18 HP, Powerlink 110 vac, 12 vdc
GT18H02	5 or 8 GPM Honda GX620

ACCESSORIES	DESCRIPTION
31848	Dual Hose, 50 ft x 1/2", with couplers
31972	Dual Hose, 25 ft x 1/2", with couplers
58633	Twinned Hose, 25 ft x 1/2", with couplers
58634	Twinned Hose, 50 ft x 1/2", with couplers
33212	Weather Cover
13360	Hose Basket Conversion Kit
52721	High Altitude (0-6000 ft) Carburetor Jet Kit for Honda
52722	High Altitude (6000-8000 ft) Carburetor Jet Kit for Honda

WARRANTY:

Stanley Hydraulic Tools and their associated parts are warranted against defects in materials and workmanship for a period of twelve months from the date of purchase. Stanley Hydraulic Tools reserves the right to repair or replace only those pars which prove to have been defective at the time of purchase. This warranty becomes void if maximum flow and pressure ratings are exceeded.

All Stanley Hydraulic Tools, parts, accessories and allied equipment are subject to design improvements, specifications and price changes at any time without notice and with no obligation to units already sold. Weights, dimensions and operating specifications listed herein are subject to change without notice. Where specifications are critical to your applications, please consult Stanley Hydraulic Tools.

Stanley Hydraulic Tools 3810 SE Naef Road Milwaukie, OR 97267 503.659.5660 Fax 503.652.1780 www.stanleyhydraulic.com