



The GT23 is an efficient continuous duty power unit that provides a single Type II or Type III hydraulic tool circuit for "long-bar" chain saws, high volume pumps, and underwater tools - or wherever 12 GPM @ 2000 psi of hydraulic power is required. World class cooling puts the GT23 far ahead of all other power units on the market.

## **Features:**

- Type II or Type III hydraulic circuit with superior cooling
- Electronically controlled engine speed provides 8 or 12 GPM
- Auto idle feature lower fuel consumption and less noise
- Tool circuit lockout during startup safety feature
- Quartz hour meter on control panel records engine run time
- Lift & Latch handle with fold-up side handles
- 35-AH sealed, non-spillable, no maintenance battery located in covered compartment
- Electric start engine with pressure lubrication system, low engine oil shut down & spin on oil filter
- In tank hydraulic filter with dipstick and easy access filter replacement



## **Specifications:**

Output Capacity	8 or 12 GPM / 30 or 45 lpm
Pressure	2,000 psi / 140 bar
Circuit Type	Open Center
Hydraulic Reservoir Capacity	3 Gallons / 11 Liters
Couplers	HTMA Flush Face
Fuel Tank Capacity	7 Gallons / 26.5 Liters
Engine	B&S 23 HP Vanguard
Weight	340 lbs / 154 kg
Length	35 in / 89 cm
Width	21.5 in / 54.6 cm
Height	29 in / 73.7 cm
Heat Rejection	5 hp

Stanley Hydraulic Tools 3810 SE Naef Road Milwaukie, OR 97267 503.659.5660 Fax 503.652.1780 www.stanleyhydraulic.com



## **ORDERING INFORMATION:**

PART NUMBER	DESCRIPTION
GT23B02	12 GPM Briggs & Stratton, 23 HP Power Unit

ACCESSORIES	DESCRIPTION
31848	Dual Hose, 50 ft x 1/2", with couplers
31972	Dual Hose, 25 ft x 1/2", with couplers
58633	Twinned Hose, 25 ft x 1/2", with couplers
58634	Twinned Hose, 50 ft x 1/2", with couplers
33212	Weather Cover
13360	Hose Basket Conversion Kit

## WARRANTY:

Stanley Hydraulic Tools and their associated parts are warranted against defects in materials and workmanship for a period of twelve months from the date of purchase. Stanley Hydraulic Tools reserves the right to repair or replace only those pars which prove to have been defective at the time of purchase. This warranty becomes void if maximum flow and pressure ratings are exceeded.

All Stanley Hydraulic Tools, parts, accessories and allied equipment are subject to design improvements, specifications and price changes at any time without notice and with no obligation to units already sold. Weights, dimensions and operating specifications listed herein are subject to change without notice. Where specifications are critical to your applications, please consult Stanley Hydraulic Tools.

Stanley Hydraulic Tools 3810 SE Naef Road Milwaukie, OR 97267 503.659.5660 Fax 503.652.1780 www.stanleyhydraulic.com