

# GTR20 POWER UNIT

**STANLEY**®



## FEATURES:

- Computerized, electronic throttle control is standard on all models. The control allows for selection of constant engine speed or automatic speed.
- All electric control system with rotary switches.
- A quartz hourmeter in the control panel records engine run time.
- The hydraulic pump is mounted directly to the engine eliminating any misalignment and ensuring long life of the drive coupling.
- An in-tank hydraulic filter continuously cleans the hydraulic fluid and assures that refill fluid passes through the filter for a clean refill.
- A 35-Ah sealed, non-spillable, no-maintenance battery is located inside a covered compartment.
- Moving the GTR around is made easy with a lift-and-latch handle.
- Pressure lubrication systems with a pressure sensing switch that will shut down the engine if the engine oil level is too low.

## SPECIFICATIONS

GTR20	
Output Capacity	2- 5 gpm/1-10 gpm
	2- 20 lpm/1-40 lpm
Pressure	2000 psi
	140 bar
Circuit Type	Open Center
Hydraulic Reservoir Capacity	3 gallons
	11 liters
Fuel Tank Capacity	7 Gallons
	26.5 liters
Weight (Wet)	330 lbs
	150 kg
Length	35 in.
	89 cm
Width	21/5 in.
	54.6 cm
Height	29 in.
	73.7 cm
Engines	Briggs & Stratton 18 HP Vanguard
Connector	HTMA Flush Faced Coupler

**NEED TO RUN TWO  
5GPM TOOLS AT ONCE?  
ANSWER - GTR20  
THE POWER OF  
HYDRAULICS**



# GTR20 POWER UNIT

**STANLEY**<sup>®</sup>

## ORDERING INFORMATION

MODEL	PART NO.	DESCRIPTION
GTR20	GTR20B06	Skid Mount Dual Circuit Briggs & Stratton 18 hp No Wheels
	GTR20B02	Dual Circuit Briggs & Stratton 18hp w/ Wheels

## ACCESSORIES

ITEM NO.	DESCRIPTION
31848	Dual Hose, 50 ft x 1/2 in., w/Couplers
31972	Dual Hose, 25 ft x 1/2 in., w/Couplers
58633	Twinned Hose, 25 ft x 1/2 in., w/Couplers
58634	Twinned Hose, 50 ft x 1/2 in., w/Couplers
13360	Hose Basket Kit
52722	High Altitude (6000-8000 ft) Carburetor Jet Kit for Honda
33212	Weather Cover

### WARRANTY:

Stanley Hydraulic Tools and their associated parts are warranted against defects in materials and workmanship for a period of twelve months from the date of purchase. Stanley Hydraulic Tools reserves the right to repair or replace only those parts which prove to have been defective at the time of purchase. This warranty becomes void if maximum flow and pressure ratings are exceeded.

