STANLEY



FEATURES:

- · Ideal for smoothing weld seams, de-burring drilled holes, cleaning castings, or any application where removal of unwanted metal is needed.
- Specifically designed to optimize power and rpm for grinding applications. The HG80 won't bog down on those tough grinding jobs. And, its compact and lightweight design helps reduce operator fatigue.
- A built-in flow control valve prevents the chance of excessive spindle speed and also protects the motor, resulting in increased tool life.



SPECIFICATIONS

HG80	
Capacity	8 in. Dia. x 1 in. Wheel
	20.3 cm Dia. Wheel
Speed	4500 rpm
	30 lpm
Input Flow	8 - 10 gpm
Range	30 - 38 lpm
Input Pressure	2000 psi
	140 bar
Weight	14 lbs
	6 kg
Length	23 in.
	58.4 mm
Width	10 in.
	25.4 cm
Height	10.5 in.
	26.7 cm
Motor	Integral
Porting	-8 SAE 0-ring
Hose Whips	Yes
Connection	HTMA Flush Face Couplers
Arbor	5/8 in11

THE PERFORMANCE TO **SMOOTH OVER ANY SITUATION -**THE POWER OF

HYDRAULICS



ORDERING INFORMATION

MODEL	PART NO.	DESCRIPTION
HG80	HG80110B	Horizontal Grinder CCW OC 8 in., Wheel
	HG80120B	Horizontal Grinder CW OC 8 in., Wheel
	GR30701S	Grinder OC/CC DRY RR 9 in. 5/8-11

ACCESSORIES

ITEM NO.	DESCRIPTION
26847	Straight Assist Handle
28598	Grind Wheel 8 x 1 x 5/8-11 (HG80)

WARRANTY:

Stanley Hydraulic Tools and their associated parts are warranted against defects in materials and workmanship for a period of twelve months from the date of purchase. Stanley Hydraulic Tools reserves the right to repair or replace only those parts which prove to have been defective at the time of purchase. This warranty becomes void if maximum flow and pressure ratings are exceeded.