STANLEY

PG10 PROFILE GRINDER



FEATURES:

- The Stanley PG10 Profile Grinder is designed to grind a wide range of rail from 90# to 140#. Adjustable flange wheels which cannot get out of adjustment ensure grinding accuracy.
- Contains a hydraulic motor specifically designed to match power and rpm for grinding applications. A built-in flow control is used to avoid excessive spindle speed.
- For added safety the PG10 features an interlocking trigger which prevents accidental engagement of the tool.
- The PG10 also features a removable wheel guard for easy access to the grinding wheel when installing and removing grinding wheels.

SPECIFICATIONS

	-
PG10	
Wheel Capacity	6 in.dia. x 3 in.
	15.2 cm dia. x 7.6
	cm
Arbor Size	5/8 in 11
Length	44 in.
	112 cm
Width	20 in.
	50.8 cm
Weight	118 lb
	53.52 kg
Optimum Flow	10 gpm
	38 lpm
Maximum Back	250 psi
Pressure	17 bar
Hydraulic	1000-2000 psi
Pressure	70-140 bar
RPM	6000 max
Motor	Integral
Porting	-8 SAE 0-ring
Connector	HTMA Flush Faced Coupler

DAYS OF HAND GRINDING WARN DOWN RAIL HEADS-OBSOLETE -

THE POWER OF HYDRAULICS

STANLEY

PG10 PROFILE GRINDER

ORDERING INFORMATION

MODEL	PART NO.	DESCRIPTION
PG05	PG10110	Profile Grinder with Shaft Wrench. Not included – Grinding Stone
	PG10110B	Profile Grinder with Shaft Wrench. Not included – Grinding Stone - AERO QUIP
	PG1011001	Profile Grinder OC, 6", 5/8-11, CE
	PG1011001A	Profile Grinder OC, 6", 5/8-11-Revised Handle

ACCESSORIES

ITEM NO	DESCRIPTION
	Grinding Stone, 6 in. dia. x 3 in. x 5/8 - 11 Arbor



WARRANTY:

Stanley Hydraulic Tools and their associated parts are warranted against defects in materials and workmanship for a period of twelve months from the date of purchase. Stanley Hydraulic Tools reserves the right to repair or replace only those parts which prove to have been defective at the time of purchase. This warranty becomes void if maximum flow and pressure ratings are exceeded.

