

STANLEY[®]

FG10 FROG GRINDER



FEATURES:

- Light Weight Construction and Upright Handle allow operator to work in a full-upright position, reducing operator fatigue and risk of back injury.
- Trigger Lock prevents accidental engagement of the tool, reducing the risk of injury.
- Built-In Flow Control prevents excessive spindle speed and reduces risk of damage to hydraulic motor.
- Meets ANSI and OSHA standards for tool type.



SPECIFICATIONS

FG10	
Wheel Capacity	6 in.dia. x 3 in.
	15.2 cm dia. x 7.6 cm
Arbor Size	5/8 in. - 11
Length	44 in.
	112 cm
Width	14.5 in.
	37 cm
Weight	85 lbs.
	41 kg
Optimum Flow	8 - 10 gpm
	30 - 38 lpm
Maximum Back pressure	250 psi
	17 bar
Hydraulic Pressure	2000 psi
	140 bar
RPM	6000 max
Motor	Integral
Porting	-8 SAE O-ring
Connector	HTMA Flush Faced Coupler

**DAYS OF HAND GRINDING
WORN DOWN FROGS -
OBSOLETE.
THE POWER OF
HYDRAULICS**

STANLEY

Stanley Hydraulic Tools | 3810 SE Naef Road | Milwaukie, Oregon 97267 | +01.503.659.5660 | 800.972.2647 | www.stanleyhydraulic.com

STANLEY[®]

FG10 FROG GRINDER

MODEL	PART NO.	DESCRIPTION
FG10	FG10110	Frog Grinder OC, 6", 5/8 - 11 thrd
	FG10110B	Frog Grinder OC, 6", 5/8 - 11 thrd- Aero Quip
	FG1011001	Frog Grinder OC, 6", 5/8 - 11 thrd- CE

ACCESSORIES

ITEM NO.	DESCRIPTION
28597	Grinding Stone, 6 in. dia. x 3 in. x 5/8 - 11 Arbor



WARRANTY:

Stanley Hydraulic Tools and their associated parts are warranted against defects in materials and workmanship for a period of twelve months from the date of purchase. Stanley Hydraulic Tools reserves the right to repair or replace only those parts which prove to have been defective at the time of purchase. This warranty becomes void if maximum flow and pressure ratings are exceeded.

STANLEYStanley Hydraulic Tools | 3810 SE Naef Road | Milwaukie, Oregon 97267 | +01.503.659.5660 | 800.972.2647 | www.stanleyhydraulic.com